




[Anfrage senden](#)
[weitere Infos](#)

Wandkonsole einfache Ausführung einsetzbar im Innen- und Außenbereich



Standardwerkstoffe: S235 feuerverzinkt oder 1.4571



Schiene	Länge
28/28	100
28/28	200
28/28	300
28/28	400

Höhe	Kopfplatte
120	120 x 40 x 6
120	120 x 40 x 6
120	120 x 40 x 6
120	120 x 40 x 6



Tragfähigkeitswerte			
F ₁ (kN)	F ₁ (kN)	F ₂ (kN)	F ₃ (kN)
2,70	1,35	1,35	0,90
1,35	0,38	0,38	0,45
9,00	0,45	0,45	0,30
0,70	0,35	0,35	0,20



Schiene	Länge
36/36	300
36/36	400
36/36	500
36/36	600

Höhe	Kopfplatte
120	120 x 40 x 8
120	120 x 40 x 8
120	120 x 40 x 8
120	120 x 40 x 8



Tragfähigkeitswerte			
F ₁ (kN)	F ₁ (kN)	F ₂ (kN)	F ₃ (kN)
2,00	1,00	1,00	0,70
1,50	0,75	0,75	0,50
1,20	0,60	0,60	0,40
1,00	0,50	0,50	0,33



Schiene	Länge
41/41	200
41/41	300
41/41	450
41/41	600
41/41	750

Höhe	Kopfplatte
125	125 x 50 x 8
125	125 x 50 x 8
125	125 x 50 x 8
125	125 x 50 x 8
125	125 x 50 x 8

Tragfähigkeitswerte			
F ₁ (kN)	F ₁ (kN)	F ₂ (kN)	F ₃ (kN)
4,24	2,06	2,06	1,43
2,75	1,38	1,38	0,90
1,90	0,95	0,95	0,45
1,38	0,69	0,69	0,30
1,13	0,55	0,55	0,38



Schiene	Länge
41/41	175
41/41	325
41/41	475
41/41	625

Höhe	Kopfplatte
180	U: 50x25x4

Tragfähigkeitswerte			
F ₁ (kN)	F ₁ (kN)	F ₂ (kN)	F ₃ (kN)
5,35	2,65	2,65	1,75
2,65	1,30	1,30	0,85
1,75	0,85	0,85	0,55
1,00	0,50	0,50	0,30